


Printer Type	T6100					
Printing Technology	Line impact dot matrix					
Print Speed (LPM)						
Upper Case						
Lower Case						
Devnagari Character Representation (Emulation Dependent)						
* Character Pitch	Draft	DP	Courier	Gothic	OCR-A*	OCR-B*
Line Pitch	1020	760	360	360	610	225
Graphics Resolution	870	600	270	270	465	160
Graphics Speed	High Speed (DP)			NLQ (Gothic)		
Fonts	415 to 320			180 to 150		
Barcodes**						
Paper Handling						
Paper Width	5, 6, 6.67, 7.5, 8.33, 8.57, 10, 12, 13.3, 15, 16.67, 17.14, & 20 cpi					
Number of Copies	1.5, 2, 3, 4, 5, 6, 7, 8, 9 & 10 lpi					
Interfacing						
Optional	Upto 240*288 dpi					
	100 inches/minute(max)					
Emulations	Draft, Dataprocessing, Gothic, Courier, OCR- A,OCR- B					
	2/5 Matrix, 2/5 Interleaved, EAN 8,EAN 13,UPC- A					
	Four tractors					
Environmental						
Acoustic	From 4.0 inch TO 17.5 inch					
Level (ISO 7779)	Original +5					
Weight						
Dimensions (HxWxD)	IEEE 1284 Parallel and Serial RS232 (both active simultaneously)					
Voltage						
Power Consumption	Fourplex printer version (Coax, Twinax, Pparallel, Serial)					
Operating Environment	Fourplex plus IBM IPDS Printer version					
MTBF	Lanplex printer version					
Consumables	(Ethernet 10Base2 and 10Base-T ,Parallel, Serial)					
	Option: In-line token ring solution					
	Tally MT660/MT690,EPSON FX,IBM Proprinter XL,					
	Printonix P600/P6000,DEC LG01,Genicom ANSI,					
	Hewlett Packard HP2564C,QMS Code V,					
	Printronix graphics language (PGL)					
	52 db(A)					
	90 Kg					
	800 mm*800 mm*848 mm (including closed pedestal)					
	90-130/180-260 V AC, 47/63 Hz (auto ranging)					

300W Printing

+10'C TO +40'C (Temperature)

10 % TO 90 % Non condensing (Relative humidity)

12,000 hours

Ribbon cartridges (Refillable)