

SPECIFICATIONS

Weight –
EPSON AcuLaser™ C3800N
25.8 Kg (30.2 Kg w / Consumables)
EPSON AcuLaser™ C3800DN
27.0 Kg (31.4 Kg w / Consumables)



OPTIONAL ACCESSORIES

550-Sheet Paper Cassette Unit C12C802291

CONSUMABLES

High Capacity Imaging Cartridge [†] Yellow	(9,000 pages [^])	1124
High Capacity Imaging Cartridge [†] Magenta	(9,000 pages [^])	1125
High Capacity Imaging Cartridge [†] Cyan	(9,000 pages [^])	1126
High Capacity Imaging Cartridge [†] Black	(9,500 pages [^])	1127
Standard Capacity Imaging Cartridge [†] Yellow	(5,000 pages [^])	1128
Standard Capacity Imaging Cartridge [†] Magenta	(5,000 pages [^])	1129
Standard Capacity Imaging Cartridge [†] Cyan	(5,000 pages [^])	1130
Fuser Unit	(100,000 pages [^])	3025
Transfer Unit	(100,000 pages [^])	3024

[^]The above figures are approximate number of sheets printed under conditions of continuous printing on A4 size paper with 5% page coverage, mono:color printing ratio = 1:1.

(Initial Imaging Cartridges: Black: 9,500 pages[^], Colour: 5,000 pages[^])

[†]Depending on various usages and environments, page yield may reduce and come to its end of service life. It may occur even with toner left due to reaching the other parts' end of service life.



EPSON is the registered trademark of SEIKO EPSON CORPORATION.

All other product names and other company names used herein are for identification purpose only and may be the trademarks or registered trademarks of their respective owners. Epson disclaims any and all rights in those marks. Scan/Print samples shown herein are simulations. Specifications are subject to change without notice.

EPSON AcuLaser™ C3800N C3800DN

PRINTER TYPE	PRINTING TECHNOLOGY	Laser Single Pass	
	RESOLUTION	4800 RIT* (*Epson AcuLaser™ Resolution Improvement Technology)	
	PRINT SPEED	Mono 25ppm, Colour 20ppm	
	FIRST PAGE OUT WARM UP TIME MAXIMUM MONTHLY VOLUME	15 Sec (Mono / Colour) 30 Sec (220 - 240V) 60,000 Pages	
PAPER HANDLING	STANDARD PAPER INPUT	700 Sheets (150 Multi-Purpose Tray + 550 Standard Paper Cassette)	
	MULTI PURPOSE TRAY	PAPER SIZE WIDTH LENGTH PAPER WEIGHT	A4, A5, B5, LT, GLT, HLT, LGL, GLG, IB5, EXE, C5, DL 76.2 - 220 mm 98.4 - 355.6 mm 60 - 216 g / m ²
INTERFACES	STANDARD PAPER CASSETTE	PAPER SIZE PAPER WEIGHT	A4, A5, B5, LT, EXE, LGL, GLG 60 - 105 g / m ²
	550-SHEET PAPER CASSETTE UNIT (OPTION)	PAPER SIZE PAPER WEIGHT	Same as Standard Paper Cassette Same as Standard Paper Cassette
	DUPLIX UNIT	PAPER SIZE	Same as Paper Cassette
	AcuLaser™ C3800DN AS STANDARD MAXIMUM PAPER INPUT	PAPER WEIGHT	64 - 163 g / m ² 1250 sheets (150 MP Tray + 2 x 550 - Sheet Paper Cassettes) 250 Sheets (Face Down)
MEMORY	STANDARD / MAXIMUM	128 MB / 1 GB	
	POWER REQUIREMENTS	ENERGY STAR COMPLIANT POWER CONSUMPTION	RATED CURRENT OPERATING STANDBY SLEEP
ENVIRONMENTAL CONDITIONS	TEMPERATURE	OPERATION	4.0A / 8.0A (220-240V)
	HUMIDITY	STORAGE	Max. 730 Wh / 750 Wh (AL-C3800N / AL-C3800DN) Ave. 347 Wh (Mono), 361 Wh (Colour) (220 - 240V) 78 Wh (220 - 240V) 17 Wh
	SOUND PRESSURE	OPERATION STORAGE OPERATING STANDBY	5 to 32 C 0 to 35 C 15 to 85% RH 15 to 80% RH 51 dB (A) 30 dB (A)
PRINTER DRIVER / UTILITY	PRINTER DRIVER	Microsoft® Windows® 98 / ME / 2000 / XP / Server 2003, Mac™ OS 9.X and Mac™ OS X	
	EPSON STATUS MONITOR	Microsoft® Windows® 98 / ME / 2000 / XP / Server 2003, Mac™ OS 9.x and Mac™ OS X	
	EPSON FONT MANAGER	Microsoft® Windows® 98 / ME / 2000 / XP / Server 2003	
	EPSON BARCODE FONTS	Microsoft® Windows® 98 / ME / 2000 / XP / Server 2003	
	EPSONNET PRINT	Microsoft® Windows® 98 / ME / 2000 / XP / Server 2003	
	EPSONNET CONFIGURATION	Microsoft® Windows® 98 / ME / 2000 / XP / Server 2003, Mac™ OS 9.x and Mac™ OS X	
	EPSONNET EASYINSTALL	Microsoft® Windows® 98 / ME / 2000 / XP / Server 2003, Mac™ OS 9.x and Mac™ OS X	
	USB MEMORY PRINT MAKER	Microsoft® Windows® 98 / ME / 2000 / XP / Server 2003	
EPSONNET WEBMANAGER EPSONNET SETUPMANAGER	Microsoft® Windows® 2000 / XP / Server 2003 Microsoft® Windows® 98 / ME / 2000 / XP / Server 2003		
EPSON WEB-TO-PAGE EPSONNET INTERNET PRINT EPSONNET NDPS GATEWAY	Microsoft® Windows® 98 / ME / 2000 / XP Microsoft® Windows® 98 Microsoft® Windows® 98 / 2000 / XP, Novell® NetWare® 5.0 / 5.1 / 6.0 / 6.5		
PRINTER CONTROL LANGUAGE EMULATIONS	STANDARD	COLOUR B / W	ESC / Page Colour™, PCL5C, PS3, PDF1.3 ESC / Page™, ESC P2™, PCLXL, FX, I239X
LCD PANELS	5-Line, 22-Digit LCD Display with 3 LEDs & 6 Buttons		
DIMENSIONS (W x D x H)	420 x 501 - 577 x 508 mm		
WEIGHT[†]	AL-C3800N	25.8 Kg (30.2 Kg w / Consumables)	
	AL-C3800DN	27.0 Kg (31.4 Kg w / Consumables)	

[†]Weight including High Capacity Imaging Cartridges.

EPSON
EXCEED YOUR VISION

INDIA – (91) 80-305-15000, CALCUTTA – 228 31589/90,
CHENNAI – 302 77500, MUMBAI – 282 61515/16/17, NEW DELHI – 306 15000
INDONESIA – (62) 21-572-3161
MALAYSIA – (60) 3-562-88288
PHILIPPINES – (632) 813-6567
SINGAPORE – (65) 6586-5500, (65) 6586-3111
THAILAND / INDOCHINA – (662) 685-9888

Dealer's Stamp