

## Software

### Firewall

- 6,000 Concurrent Connections
- Stateful Inspection Firewall
- 3-Level Preset Security Policies
- Firewall Customization Wizard

### VPN

- 20Mbps Performance (3DES)
- Site-to-site IPSec VPN
- Remote Access VPN Gateway
- 5 VPN-1 SecuRemote Client Licenses Included
- AES, 3DES, and DES Encryption
- Authentication: SHA1/MD5
- IPSec NAT Traversal
- VPN Site Wizard

### Networking

- WAN Access Protocols:
  - Static IP
  - PPPoE
  - Telstra
  - DHCP
  - PPTP
- Traffic Shaper (QoS) Predefined Classes
- Static NAT
- Hide NAT
- PAT
- DHCP Server
- MAC Cloning
- Static Routes
- Internet Connection Setup Wizard
- Digital Certificates (X.509)
- Failover WAN (Ethernet or Dialup)

### Logging and Monitoring

- Advanced Attack & Audit Logs
- Syslog Logging
- Graphical Map of Network & VPN Tunnels
- Packet Capture Utility

### Local Management

- Web-based Management
- HTTPS Remote Management
- CLI (Command Line Interface)
- SSH Remote Management

### Upgrades

- User limit Upgradeable (10, 25, Unlimited)
- Services Upgradeable (Web Filter, Antivirus)

### Printer Server

- 2 USB Ports

### WLAN Security

- VPN over Wi-Fi
- WEP (64, 128-bit)
- WPA, WPA-PSK
- WPA2, WPA2-Personal

## Physical & Environmental

### Device Ports

- WAN: 1 10/100BASE-TX Port
- LAN: 4 10/100BASE-TX Ports
- DMZ/WAN2: 10/100BASE-TX Port
- WLAN: Wi-Fi 802.11b/g/108G
- Console Port: Serial COM Port
- USB Port: 2 x USB 2.0

### Diagnostic LED

- Power
- WAN (Link/Activity per Port) (2)
- LAN (Link/Activity per Port) (8)
- DMZ/WAN2 (Link/Activity per Port) (2)
- VPN
- Serial
- USB

### Power Input

- External Power Supply (5VDC, 3.0A)

### Power Consumption

- 15 Watts Max.

### Dimensions

- 7.875" x 5.0" x 1.25"

### Weight

- 1.8 lbs

### Temperature

- Operating: 32°F to 140°F
- Storage: -4°F to 158°F

### Humidity

- 5% to 95% (Non-Condensing)

### Emission (EMI)

- FCC Class B
- CE Class B

### Safety

- UL
- LVD (EN60950)