

Technical Specifications

Standards

- IEEE 802.3
- IEEE 802.3u

Ports

- 8 10/100 LAN
- 1 10/100 WAN
- 1 USB

Firewall Mode of Operation

- Layer 3 Mode: Route Mode, NAT Mode
- Network Address Translation (NAT)
- Port Address Translation (PAT)
- Port Forwarding

VPN Security

- VPN Tunnels: 8 (IPSec, PPTP, L2TP)
- IPSec LAN-to-LAN / Roaming User
- PPTP/L2TP Server/Client
- IPSec/PPTP/L2TP Pass-through
- IPSec NAT-Traversal
- DHCP over IPSec
- Encryption Transform: DES, 3DES, AES
- XAUTH (Extended Authentication) for IPSec Authentication

Firewall Security

- Stateful Packet Inspection (SPI)
- Network Address Translation (NAT)
- Internal User Database (20 Records)

Network Service

- Static IP address
- PPPoE for xDSL
- DHCP Client for WAN Interface
- BigPond Cable, Telia Compliance
- Internal DHCP Server
- DHCP over IPSec
- Static Routes
- DNS Resolving of Remote Gateway
- Dynamic DNS Poster

Device Management

- Internet Explorer v6 or later; or other Java-enabled Browsers

LEDs

- Power
- Status
- LAN
- WAN
- USB

Certifications

- FCC Class B

Operating Temperature

- 32°F to 131°F (0°C to 55°C)

Operating Humidity

- 95% Maximum (Non-condensing)

Dimensions

- Item (WxDxH): 4.7 x 7.5 x 1.2 inches
- Packaging (WxDxH): 8.2 x 10.8 x 2.7 inches

Weight

- Item: 0.67 lbs

- Packaging: 1.91 lbs

Warranty

- 1 Year Limited*