



Print Head Type	9 Pin
Print Direction	Bi-directional logic seeking
Print Width	80 column
Print Head Life	200 Million Characters
<b>Print Speed</b>	
Character Pitch (dpi)	10      12      15
High Speed Draft (cps)	380    450    -
Draft (cps)	300    360    450
Letter Quality (cps)	63      75      -
<b>Resident Printer Fonts</b>	
Draft	Draft, High Speed Draft
Near Letter Quality	Roman, Sans Serif, Script
Barcode	Code 3 of 9
<b>Paper Handling</b>	
Paper Path Standard	Top, Rear, Bottom
Continuous-Tractor Feed Standard	Convertible Push & Pull
<b>Paper Size</b>	
Cut Sheets Width	3.5-10"
Continuous Form Width	3.5-10"
Paper Thickness	Tractor feed - 0.3mm(max) Friction feed - 0.3mm(max)
Copy Capability*	1+ 4 with carbon
<b>Consumables - Ribbon</b>	
Type	Unique TVS Ribbon Cassette with Replaceable Inkbank
Colour	Standard Black
Ribbon Life	40 Million Characters**
Cassette Refill Mode	Through Inkbank
Inkbank Life	10 Million Characters***
Input Buffer (Kilo Bytes)	100 KB
<b>Reliability</b>	
MTBF (Power on Hours)	15000 POH
Acoustics - Noise Level	55db(A)
Emulation	Epson ESC P, IBM Proprinter
<b>Interface</b>	
Standard	Centronics IEEE -P1284A Parallel
Optional	RS 232C Serial
<b>Software Specifications</b>	
Drivers	Windows 95, 98, NT 4.0, 2000, Me, XP, Linux Redhat

Electronic Guide HTML Based

**Electrical Specifications**

Operating Voltage 150 V AC-270 V AC

Mains Frequency 47-63 Hz

Power (Standby) 12W

**Environmental - Operating Conditions**

Temperature +5 to +45 deg C

Relative Humidity 10% to 80%

**Physical Dimensions**

Width x Depth x Height (mm) 433 x 379 x 147

Weight (kg) 5.7

---