

High Speed Dot for Billing



Configuration	9 wire – 80 column
Print Head Life	PTFE Coated, 200 Million Character life at Draft 10 cpi mode
Top Print Speed	380 cps @ 12 cpi High Speed Draft mode
Character Font	
Draft	Standard 10, 12, 15, 17 & 20
HS Draft	Standard 10, 12
Near Letter Quality	Quality Roman 10, 12, 15, 17 & 20 Sans Serif 10, 12, 15, 17 & 20 Script 10, 12, 15, 17 & 20
Paper Paths	Top Friction Mode– For Single sheet Front Tractor Mode– For continuous stationary Rear Friction Mode–For roll paper
Paper Size	Continuous Form Width : 3.5"– 10" Cut Sheets & Roll Paper : 2.25"– 8" Paper Thickness Tractor & : 0.3mm Friction Speed
Copy Capability	1 + 3 with carbon (max. paper thickness 0.3mm)
Paper Tear Bar	Integrated - Metallic (Stainless Steel)
Printer Stand	Integrated, foldable
Tractor(s)	
	Integral Flat front
Paper feed speed	5 IPS during form feed
Menu settings	3 MACROS provided in the non-volatile memory of the printer to store customized settings
Emulation	Epson ESC/P, IBM
Drivers	Windows 95, 98, 98SE, 2000, Me Windows XP & Window NT 4.0, Linux Redhat
Buffer Memory	Standard : 10 Kbytes
Noise	Noise level : < 49 dB (A) in ISO 7779 pattern sonic pattern test
Physical	Dimensions : (W x D x H) mm 444 x 232 x 220 mm Weight : 4.5 Kgs
Environmental	Temperature : +0 Deg. C to + 50 Deg. C Humidity : 10% to 90 % RH
Ribbon	Type : Unique Inkbank, Cassette (Patented) Ribbon Life : 40 Million Characters at 10cpi Draft with 3 additional inkbanks Refill mode : Through InkBank
Interface	Standard : Centronics IEEE 1284A, USB Ver 2.0 & RS232C Serial interface
Power Supply	160 ~ 270V AC
Mains Frequency	47 ~ 63 Hz
Standby Power Consumption	~5 Watts
MTBF	10,000 POH @ 33% print density and 25% duty cycle (excluding Print Head).
Standard Configuration	Printer, TVS Ribbon Cassette, External Power adapter Parallel Interface Cable, Printer Software CD-ROM Quick Reference Guide, Single Sheet Feed Holder Roll paper Feeder Kit

Consumables

Ribbon Cassette, Inkbank

Certifications

FCC Class A, CE, IEC 60950

Accessories

USB Interface Cable
RS232C Serial Interface cable